

MSDS: MATERIAL SAFETY DATA SHEET



WASHINGTON ALDER LLC

13527 Farm to Market Road, Mt. Vernon, WA 98273

Phone: 360-542-1900 Fax: 360-424-9047

Email: Info@BuyAlder.com Websites: www.Washington-Alder.com and <http://www.buyalder.com/>

SECTION 1: PRODUCT IDENTIFICATION

Product Name:	Wood Dust
Synonyms:	Sawdust, sander dust
Description	Wood dust includes dust from all hardwoods. Consists of particles generated by any manual or mechanical cutting or abrasion process performed on wood.
Prepared By:	Legal Compliance Department

SECTION 2: HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

CAS#	Component	Percent
N/A	Wood / Wood Dust	92-100%

SECTION 3 -PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Light to dark colored granular solid	Specific Gravity:	Not Available
Odor:	Wood odor-dependant on species	Vapor Pressure:	Not Available
Boiling Point:	Not Applicable	Vapor Density:	Not Applicable
Melting Point:	Not Applicable	Density:	Not Applicable
Freezing Point:	Not Applicable	% Volatile by Volume:	Not Applicable
Weight per Gallon	Not Applicable	Solubility (H ₂ O):	Not Applicable
Evaporation Rate:	Not Applicable	Reactivity (H ₂ O):	Not Applicable

SECTION 4: FIRE AND EXPLOSION HAZARD

Flash Point	Method	Upper/Lower Flammable Limit	Auto-ignition	Rate of Burn
Not Applicable	Not Applicable	Lower: 40.0 Q/m ³	400-500 deg. F	Not Available

Unusual Fire and Explosion Hazards! Wood is combustible when exposed to heat or flame. Wood dusts may form explosive mixtures with air in the presence of an ignition source.

Fire Fighting Equipment and Extinguishing Media: Use water to wet down wood to reduce the likelihood of ignition. Remove burned or wet dust to open area after fire is extinguished. Fire fighters should use full protective clothing including self-contained breathing apparatus

SECTION 5: HEALTH HAZARDS AND FIRST AID

WARNING! Wood dust may form an explosive mixture with air.

Use exhaust ventilation when cutting, sawing or grinding in an enclosed area. Wood dust may cause irritation to eyes, skin, and upper respiratory tract. When cutting, sanding, or grinding avoid inhalation and wear safety glasses. Handling may cause splinters, use puncture resistant gloves.

	Signs and symptoms of acute overexposure	First Aid Measures
Eyes:	Wood dust may cause irritation to the eyes. Symptoms can include irritation, redness, scratching of the cornea, and tearing	Immediately flush eyes with water for at least 15 minutes. Seek medical attention if symptoms persist
Skin:	Wood dust may cause irritation to the skin. Mechanical rubbing may increase skin irritation. Some wood species and their dusts may contain natural toxins, which may cause dermatitis or allergic reactions in sensitized individuals.	For skin contact flush immediately with soap and water, continue at least 15 minutes. If irritation persists, get medical attention immediately. If wood splinters are injected under the skin, get medical attention immediately.
Ingestion:	Ingestion of wood dusts is unlikely. If ingestion does occur, slight gastrointestinal irritation may result Certain species of wood and their dusts may contain natural toxins, which can have adverse effects on humans.	If the material is swallowed, get medical attention or advice. Do not induce vomiting.
Inhalation:	Wood dust is irritating to the nose throat and lungs. Symptoms may include nasal dryness, deposits or obstructions in the nasal passages, coughing, sneezing, dryness and soreness of the throat and sinuses, hoarseness, and wheezing. Some species may cause allergic respiratory reactions with asthma-like symptoms in sensitized individuals.	If dusts are inhaled, remove person to fresh air. If symptoms persist, seek medical attention.

Note to Physician: Respiratory ailments and pre-existing skin conditions may be aggravated by exposure to wood dust
 Medical Conditions Generally Aggravated by Exposure to Wood Dust: Pre-existing eye, respiratory system and skin conditions.
 Chronic Overexposure: Wood dusts may be irritating to the eyes, skin and respiratory tract. Prolonged or repeated inhalation of wood dust may cause respiratory irritation, recurrent bronchitis, and prolonged colds. Depending on the species of wood, recurrent exposure may cause allergic skin and respiratory reactions in some individuals.

Carcinogenicity: Prolonged exposure to wood dust by inhalation has been reported to be associated with nasal and paranasal cancer. Wood dust is classified as a carcinogen by ACGIH, NIOSH, and IARC. This classification is based on an increased

incidence of nasal and paranasal cancer in people exposed to wood dusts. Carcinogenicity of wood dust: ACGIH -A1 Confirmed Human Carcinogen (related to wood dusts-hard wood ; NIOSH Occupational carcinogen (related to wood dust); IARC - . Monograph 62, 1995 (related to wood dust)(Group 1 (carcinogenic to humans)).

SECTION 6: EXPOSURE CONTROL MEASURES/PERSONAL PROTECTION

Eyes/Face:	Wear Safety glasses with side shields when handling, cutting, sanding, or grinding this material. Use a face shield for processes that may generate excessive dusts and splinters.
Skin:	Wear puncture resistant work gloves, such as leather when handling.
Respiratory:	Respirators must be worn if the ambient concentration of airborne contaminants exceeds prescribed exposure limits. Dust masks may be worn to avoid inhalation of nuisance dust. Dust masks are not adequate protection in environments above the occupational exposure limit
Ventilation:	Cutting, grinding or sanding should be done outdoors or in a well ventilated area.

Component Exposure Limits

Component		OSHA		ACGIH	
		PEL	STEL	TLV	TLV STEL
Wood / Wood dust	Hardwoods	15 mg/m ³ total dust 5 mg/m ³ respirable fraction (as a nuisance dust)	6 mg/m ³ TWA	1 mg/m ³ TWA	N/A

SECTION 7: SAFE HANDLING, STORAGE, DISPC;>SAL, AND ACCIDENTAL RELEASE MEASURES

Handling Procedures:	Do not generate airborne dusts in the presence of an ignition source when sawing, cutting or grinding wood. Practice good personal hygiene procedures. Avoid contact of wood dusts with skin and eyes. Avoid breathing wood dusts. Do not eat, drink, or smoke when handling this product or in areas where dusts of this product are present
Storage Procedures	Maintain good housekeeping procedures, such as sweeping regularly to avoid accumulation of dusts. Store in a cool, dry area away from excessive heat, sparks, and open flame.
Disposal Procedures	Dispose of waste material according to local, State, and Federal Regulations.
Accidental Releases	No containment measures are necessary

SECTION 8: REGULATORY INFORMATION

OSHA:	Untreated wood and wood products are considered manufactured articles and are exempt under OSHA's Hazard Communication Standard 29 CFR 1910.1200. Wood dust, a by-product generated from sawing, sanding or machining wood and wood products, is considered hazardous and is regulated under the Hazard Communication Standard 29 CFR 1910.1200.
SARA:	Not Regulated.
DOT:	Not Regulated.
STATE:	California Proposition 65 Warning: This product contains a chemical (wood dust) known to the State of California to cause cancer.

Sample Warning Label:

WARNING:

Drilling, sawing, sanding or machining wood products generates wood dust, a substance known to the State of California to cause cancer. Avoid inhaling wood dust or use a dust mask or other safeguards for personal protection.

California Health and Safety Code Section 25249.6

NOTICE: THE INFORMATION AND RECOMMENDATIONS SET FORTH ARE BELIEVED TO BE ACCURATE, HOWEVER, WASHINGTON ALDER LLC. MAKES NO WARRANTY WITH RESPECT TO AND DISCLAIMS ALL LIABILITY FROM RELIANCE ON THE INFORMATION. REVISED: 16 DECEMBER 2010



BUYALDER.COM

